




SINCE 1990
POWDER EXTINGUISHER
 ABC DRY POWDER 滅火器

Agent

ABC dry chemical is a multipurpose extinguishing agent that is suitable for use on Class A,B,C,E



1. REFILL AFTER ANY USE. CHECK PERIODICALLY
2. CHECK CARTRIDGE WEIGHT ANNUALLY
3. USE ONLY PRODUCTS AND SPARE PARTS IN CONFORMITY WITH THE AGREED MODEL
4. PROPELLANT : NITROGEN GAS
5. TEMPERATURE RANGE: -20°C ~ +55°C



Portable Dry Powder Fire Extinguisher
 手提式幹粉滅火器

型號 Model	外徑 Out-diameter	容積 Volume	瓶高 Cylinder Length	瓶重 Cylinder Weight	滅火劑重量 Extinguisher Weight	滅火劑重量 Filling Weight	溫度範圍 Temperature Range	最大工作壓力 Max Working Pressure	測試壓力 Test Pressure	最小壁厚 Min Wall-thickness	滅火級別 Fire Class	包裝尺寸 Packing Size
MFZ/ABC1	φ88mm	1.3L	310mm	0.5kg	1.5kg	1KG				≥0.8mm	1A21B	50X20X33cm
MFZ/ABC2	φ110mm	2.6L	385mm	1.2kg	3.2kg	2KG	-20°C +55°C	1.2MPa	2.1MPa	≥1.08mm	1A21B	385X255X350cm
MFZ/ABC3	φ130mm	3.9L	420mm	1.5kg	4.8kg	3KG				≥1.14mm	2A34B	430X270X140cm
MFZ/ABC5	φ140mm	6.5L	526mm	2.5kg	7.5kg	5KG				≥1.25mm	3A89B	520X320X160cm

ZHEJIANG ZHEAN FIRE FIGHTING EQUIPMENT CO.,LTD.
 浙江浙安消防設備有限公司



SINCE 1990
CO2 EXTINGUISHER
 CARBON DIOXIDE 滅火器

Agent

Carbon dioxide is the trusted non-conductive clean agent and is most effective for dealing with electronic equipment fires. CO2 is suitable for use on Class B,C,E



INSTRUCTION

1. Fire extinguishing agents:CO2
2. Capacity: 2-0.15kg;3-0.15kg ;5-0.15kg;
3. Service temperature:-10°C~+55°C
4. Hydrostatic test: Having hydrostatic test at 22.5MPa is required every 5 years or before refilled. The rate of remain deformation should not more than 6%.

MAINTENANCE

At least check up the weight of the extinguisher every half year and be repaired if leakage exceeds 10%.
 Keep it safe. It must be recharged or maintained after discharging.

Portable CO2 Fire Extinguisher
 手提式CO2滅火器

型號 Model	外徑 Out-diameter	容積 Volume	瓶高 Cylinder Length	瓶重 Cylinder Weight	滅火劑重量 Extinguisher Weight	滅火劑重量 Filling Weight	溫度範圍 Temperature Range	最大工作壓力 Max Working Pressure	測試壓力 Test Pressure	最小壁厚 Min Wall-thickness	滅火級別 Fire Class	包裝尺寸 Packing Size
MT/2	φ110mm	3L	480mm	4.50KG	6.5KG	2KG				3.6mm	21B	13X27X53cm
MT/3	φ116mm	4.5L	630mm	7.00KG	10KG	3KG	-10°C +55°C	17.5MPa	22.5MPa	3.6mm	21B	15X33X57cm
MT/5	φ150mm	7.5L	650mm	12.00KG	17KG	5KG				4.3mm	34B	17X17X66cm

ZHEJIANG ZHEAN FIRE FIGHTING EQUIPMENT CO.,LTD.
 浙江浙安消防設備有限公司